





Page 1 of 2

Certificate of Calibration

Reference No R124140719 Cert. No. PSYP- 24058883

Date of Issue

06 Aug 2024

Customer

PRO LAB ENGINEERING SERVICES SDN BHD

No.21-G

ID: 039228

Jalan Bidara 8 Saujana Utama 3

47000 Sungai Buloh

Selangor

Instrument

Test Sieve

Model

NL SCIENTIFIC

Serial No

22071407

Control No

CA5590F

Equipment ID

Capacity/Range

N/A 425 µm

Date of Receipt

02 Aug 2024

Date of Calibration

06 Aug 2024

Recalibration Date

Customer to Determine

(Specified by Customer)

The User should be aware there are many factors may cause this instrument to drift out

of calibration limits prior to the stated recalibration date.

Condition of Instrument

Before Calibration After Calibration

Good Physical Condition Calibrated and Serviceable

Location of Calibration

Calibration Environment

Trescal Laboratory (20.0 ± 1.0) °C, (55 ± 15) %rh

Calibration Method

LCP 01430

Reference Standard Used

Reference Instrument Profile Projector

Equipment ID

PH-DS-PP1

Control No CA04020

Certificate No

PSYP-23073126

Traceable to

Due Date 13 Oct 2024 **NMIM**

Calibrated By

Siti Nadia Binti Mohd Mahadi

Approved Signatory

Aida Binti Ismail

The reported expanded measurement uncertainty is stated as the standard measurement uncertainty multiplied by the coverage factor k such that the coverage probability corresponds to approximately 95%

This certificate is issued in accordance with the laboratory accreditation requirements of Skim Akreditasi Makmal Malaysia (SAMM) of Standards Malaysia which is a signatory to the ILAC MRA. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Metrology Institute of Malaysia (NMIM) and other recognised national metrology institutes. Copyright of this certificate is owned by the issuing laboratory and may not be reproduced other than in full except with the prior written approval of the Head of the issuing laboratory.







Certificate of Calibration

Control No. CA5590F

Cert. No. PSYP-24058883

Page 2 of 2

Instrument Calibrated

TYPE OF TEST SIEVE	WOVEN WIRE CLOTH		
NOMINAL APERTURE SIZE	425	μm	

ACCURACY TEST					
APERTUR	E SIZE	NOMINAL VALUE	REFERENCE MEASURED VALUE	DEVIATION FROM NOMINAL	SPECIFICATION ±
A)/FDA 0F	WARP	425	420.7	-4.3	± 14.0
AVERAGE WEF	WEFT		425.6	0.6	
MAXIMUM	WARP		9.0		26.8 MAX
STANDARD DEVIATION W	WEFT		8.8	-	20.0 WAX
Measurement l	Jncertainty	= 2.1 µm	S TO IMPRO	VE YOUR P	ERFk=2/A

Remark: (*) mean Out of Specification

Info :

- 1. Aperture Size: Dimension defining an opening in a sieving medium.
- 2. Aperture Size Average: Average size of the aperture of the woven wire cloth.
- 3. Warp: All wires running lengthwise of the cloth as woven; Weft: All wires running crosswise of the cloth as woven.
- 4. Aperture Size Maximun Standard Deviation: calculated from the measurement of the number of apertures.
- 5. Uncertainty: Parameter, associated with the result of measurement, that characterises the dispersion of the value that reasonably be attributed to the measurand.

ACCEPTABLE TO USE

Izatul Azira

Lab Manager/Approved Signatory
PRO LAB ENGINEERING SERVICES SDN BHD

The reported expanded measurement uncertainty is stated as the standard measurement uncertainty multiplied by the coverage factor k such that the coverage probability corresponds to approximately 95%

This certificate is issued in accordance with the laboratory accreditation requirements of Skim Akreditasi Makmal Malaysia (SAMM) of Standards Malaysia which is a signatory to the ILAC MRA. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Metrology Institute of Malaysia (NMIM) and other recognised national metrology institutes. Copyright of this certificate is owned by the issuing laboratory and may not be reproduced other than in full except with the prior written approval of the Head of the issuing laboratory.